


IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158 Fax: 86-552-3822922

TDS of Methyl Low Hydrogen silicone oil IOTA203

Structure:



Technical index:

Viscosity, 25°C, mm2/s	80-120
Hydrogen content, %	0.18/0.36/0.50/0.75
Density , 25°C, g/cm2	0.98~1.10
Refractive index, 25°C	1 . 390~1 . 410

Properties and Uses:

1. Low Hydrogen silicone oil t is non-toxic and odorless, has active group, can react with double bond and hydroxy group under the action of catalyst;


2. Low Hydrogen silicone oil is the basic material of foam levelling agent, defoamer, Water soluble silicone oil, pure bright ceramic antifouling agent products, and the crosslinking agent of addition silicone rubber.

Packing, storage and transportation:

1. Keep in cool, dry, ventilated and non-flammable place. Far away from fire, heat source. Storage temperature<30°C.

2. 200L plastic drum (Net W.T. 200KG/drum) sealed tightly, no mix with anti-oxidant, acid and edible chemical materials.





IOTA CORPORATION LTD.

安徽省蚌埠市高新区兴中路 985 号 日月科技园 电话: 86-552-3827158 传真: 86-552-3822922

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158 Fax: 86-552-3822922

3. The lighting, ventilation facilities in In the storage room should adopt explosion-proof

products. Load gently, Prevent packaging and container from damage,

4. Non-Hazardous chemicals.

For details, please contact,

IOTA CORPORATION LTD.

Add: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Mobile/Wechat: 0086-15255260163

QQ: 3374697933

Email: info@htvsilicone.com

Website: www.htvsilicone.com